



PRODUCT INFORMATION

MEASUREMENTS

	Length	Width	Depth	Weight
20W	120mm	107mm	180mm	2.5kg
40W	268mm	203mm	161mm	3.8kg
60W	293mm	203mm	161mm	5.0kg
80W	418mm	203mm	161mm	10.2kg
100W	518mm	203mm	161mm	12.0kg

LIGHT SOURCE

Nichia High Power LED

HOUSING

Aluminium alloy and adjustable mounting bracket

BRACKET MATERIAL

ST12

MOUNTING

Standard bracket for wall/ceiling mount

FRAME COLOUR

Silver

IP RATING

IP66

OPERATING TEMP

-40°C to 55°C

TECHNICAL SPECIFICATIONS

INPUT VOLTAGE

85-277VAC, 50/60Hz or 24VDC

DIMMABLE OPTIONAL

5-100%, RGB with DMX 512

LIFESPAN

50,000 hours

EFFICACY

100lm/W

POWER

20W, 40W, 60W, 80W, 100W


BEAM ANGLE

10°, 40°, 40° Elongated

CCT

5,000-5,500K Cool White*
4,000-4,500K Natural White
2,700-3,000K Warm White
RGB

SCHEMATIC OF MULTI 20W



SCHEMATIC OF MULTI 80W



PRODUCT CODE BUILDER

E.G. NEBULA-M40W-40CW-S

PRODUCT CODE	POWER	BEAM ANGLE	CCT	TRIM	DIMMING
NEBULA-M	20W	-10	-WW (Warm White)	-S (Silver)	-DD (DALI)
	40W	-40	-NW (Natural White)		-D (0-10V)
	60W	-40E	-CW (Cool White)		-P (PWM)
	80W		-RGB		
	120W				

TYPICAL APPLICATIONS

